

RAVENOL TTC Hot Climate -15C Protect C11



1,5 l

Vendor:
1410106-150



5 l

Vendor:
1410106-005



10 l

Vendor:
1410106-010



20 l

Vendor:
1410106-020



60 l

Vendor:
1410106-060



208 l

Vendor:
1410106-208



1 000 l

Vendor:
1410106-700

RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without phosphates, nitrites and amines. This product is

formulated based on a proven inhibitor development as an extended life radiator antifreeze.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

Application Note

RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines. Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C** to radiator to fill line.

Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

Characteristics

Title	Value	Audit
ASTM	D1384, D2570, D2809, D3306, D4985, D6210 Type 1-FF	
Համապատասխանում է արտադրողի պահանջներին	AFNOR R15-601, BS 6580 (GB), CUNA NC 956-16 (Italien), Chrysler MS-7170, Fiat 9.55523, Fiat PARAFLU 11, Ford WSS-M97 B51-A1, IVECO 18-1830, JIS K 2234 (Japan), MAN 324 Type NF, O Norm V 5123, SAE J 1034, UNE 25-361 (Spanien), VW TL 774-C	
Համապատասխանում է	Suzuki	
Հատուկ հզորություն 20°C-ի դեպքում	1045 գ/սմ³	EN ISO 12185
Գույն	yellow green	տեսողական
pH արժեքը 20 °C-ում	7,0-8,4	ASTM D1287
Սառեցման կետ	-15 °C	ASTM D1177

Out of production

Product	Vendor	Barcode
1,5 լ	1410106-150-01-999	
5 լ	1410106-005-01-999	
10 լ	1410106-010-01-999	
20 լ	1410106-020-01-999	
60 լ	1410106-060-01-999	
208 լ	1410106-208-01-999	