

RAVENOL LTC HOT CLIMATE-15C Protect C12++

1 lVendor:
1410127-0101,5 lVendor:
1410127-150Vendor:
1410127-150-01-9995 lVendor:
1410127-005
Vendor:
1410127-005-01-99920 lVendor:
1410127-020
Vendor:
1410127-020-01-99960 lVendor:
1410127-060
Vendor:
1410127-060-01-999208 lVendor:
1410127-208
Vendor:
1410127-208-01-9991 000 lVendor:
1410127-700

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C is a ready to use, prediluted with water, eco-friendly 1.2-Ethanediol (monoethylene glycol) based coolant for cooling circuits in combustion engines which

provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development by combining silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C protects the cooling system from rust, frost, and in summer, from overheating.

Application Note

RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL LTC Lobrid Tech. Coolant HOT CLIMATE -15°C** to radiator to fill line.

Characteristics

- Excellent for all-aluminium engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in cooling systems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

Characteristics

Title	Value	Audit
Համապատասխանում է արտադրողի պահանջներին	Chrysler MS-90032, DTFR 29C120 (MB 325.5), DTFR 29D120 (MB 326.5), MAN 324 Type Si-OAT, MB 325.5, MB 326.6 (Premix), Scania TB 1451, VW G 012 A8G, VW G 013 A8J, VW TL 774-G, VW TL 774-J	
Հասուկ հզորություն 20°C-ի դեպքում	1043 q/սմ³	EN ISO 12185
Գույն	Violet	Մետողական
pH արժեքը 20 °C-ում	8,0	ASTM D1287
Սառցման կետ	-15 °C	ASTM D1177

Out of production

Product	Vendor	Barcode
1 L	1410127-010-01-999	
60 L	1410127-060-01-995	
208 L	1410127-208-01-995	